

W0078

Multi-Function Adjustable Wall
Washing Wall Light / Landscape Light



GRE Lighting

R & C Agency International
Lighting Specialists for over 15 years




Description: IP56 Ceiling washing or wall washing adjustable wall &/ landscape light (LED compartment is IP66). Neat and clean design. Versatile, can be mounted on wall, ground or transform into a bollard. The head can swivel to 180 degree for great scale of lighting direction. Illumination with higher central intensity to help emphasise object or other architectural elements.

LED Type: SMD
Material: Die-cast Aluminium
Dimmable: Yes




Item Code	Wattage	Input	Lumen Output	CCT	Fitting Colour	Size L x W x H
W0078	27W	700mA, 34.8-38.4V	2900 Lm / 2987 Lm	3000K / 4000K	Black / White	230 x 45 x 250 mm




Up Floodlights

With its higher central intensity, up-lights the ceiling to brighten the space indirectly to improve the atmosphere. The distance (d) of the luminaire to the ceiling should be at least 1.5m.



Down Floodlighting

To light the floor with sufficient brightness, it's suggested to install the luminaire at 1.5 meter height to prevent uncomfortable glare.



Wall Floodlighting

To keep uniform vertical illuminance with 4.5 meter height (h), the distance (d) from the wall should be at least 1 meter, the spacing for 2 luminaires shall be 1.5 meter. gives a higher contrast effect a higher contrast effect

R&C AGENCY INTERNATIONAL

94 Wecker Road,
Mansfield, QLD, 4122

Email: sales@rcagency.com.au
Ph: (07) 3216 2888
Fax: (07) 3216 2999

Opening Hour:
8:00am to 4:30pm Monday to Friday
*Showroom by appointment only