

F7030N Optic Spot



GRC Lighting

R & C Agency International
Lighting Specialists for over 15 years



AP-EN

AP-MB

Optional mounting plate or mounting box with in-built transformer.

Description: Die-cast aluminium spotlight complete with spike. Features twist lock lens cap and elbow adjustment.

Material: Aluminium, Tempered glass lens



Item Code	Max. Lamp Wattage	Lamp Base	Input	Fitting Colour	Head Size D x L
F7030NBK	LED 5-10W	MR16	12V	Black	76 x 83 mm

MR16 LED Globe(s) to suit the fittings



LED20MR16



LED216-V4



LED216-V5




LEDMR165W
LEDMR1610W



LEDMR165W-IP65

Installation of Inground Lighting



Please ensure any in-ground light fitting is installed with adequate drainage and excess water does not accumulate beneath the fitting. Use some form of 10cm depth aggregate (gravel) for drainage.

Cable Connections for Inground & Exterior Lighting

IP68 connectors / weatherproof box must be used for installation of all exterior lights. Refer to page 188 for more information

R&C AGENCY INTERNATIONAL

94 Wecker Road,
Mansfield, QLD, 4122

Email: sales@rcagency.com.au
Ph: (07) 3216 2888
Fax: (07) 3216 2999

Opening Hour:
8:00am to 4:30pm Monday to Friday
*Showroom by appointment only