

F7150 F7160 Shield Flood



GRE Lighting

R & C Agency International
Lighting Specialists for over 15 years



F7150

F7160



AP-EN

AP-MB

Optional mounting plate
or mounting box with in-
built transformer.

Description: Die-cast aluminium spotlight complete with spike. Features twist lock hooded lens cap elbow adjustment and 1.5 metre lead.

Material: Aluminium, Tempered glass lens



Item Code	Max. Lamp Wattage	Lamp Base	Input	Fitting Colour	Size
F7150	MR16 LED 5-10W	MR16	12V	Black	76 (D) x 130 mm (Head only)
F7160	MR16 LED 5-10W	MR16		Black, Silver	76 (D) x 130 mm (Head only)

MR16 LED Globe(s) to suit the fittings



LED20MR16



LED216-V4



LED216-V5




LEDMR165W
LEDMR1610W



LEDMR165W-IP65

Installation of Inground Lighting



Please ensure any in-ground light fitting is installed with adequate drainage and excess water does not accumulate beneath the fitting. Use some form of 10cm depth aggregate (gravel) for drainage.

Cable Connections for Inground & Exterior Lighting

IP68 connectors / weatherproof box must be used for installation of all exterior lights. Refer to page 188 for more information

R&C AGENCY INTERNATIONAL

94 Wecker Road,
Mansfield, QLD, 4122

Email: sales@rcagency.com.au
Ph: (07) 3216 2888
Fax: (07) 3216 2999

Opening Hour:
8:00am to 4:30pm Monday to Friday
*Showroom by appointment only