LED321-350MA LED Micro **Uplighter**





1W High power LED mini in ground up lighter with moutning clips Description:

Material: 316 grade Stainless Steel housing, tempered glass lens

Include Driver:

Inclusion: 1000 mm double insulated cable


Connection Method: **Series Connection**

IP
68

Item Code	Wattage	Input	Colour Temperature	Fitting Colour	Size D x H	Cut Size D
LED321-350MA	1W	350mA	3000K / 6000K / Blue	Stainless Steel	31 x 45 mm	26 mm

350mA LED DRIVER (s) to suit 1W fittings									
Non-Dimmable Drivers		Dimmable Drivers							
CODE	QTY	CODE	QTY						
LEDDRIVER9350KL	3	LEDDR16350DT	5						
LEDDRIVER12350	4	LEDDR28350DT	9						
LEDDRIVER24350	8	LEDDR45350DT	15						
LEDDR37350IP	12								

Installation of Inground Lighting



Please ensure any inground light fitting is insatlled with adequate drainage and exceess water does not accumulate beneath the fitting. Use some form of 10cm depth aggregate (gravel) for drainage.

Cable Connections for Inground & Exterior Lighting

IP68 connectors / weatherproof box must be used for installation of all exterior lights. Refer to page 188 for more information

R&C AGENCY INTERNATIONAL

94 Wecker Road, Mansfield, QLD, 4122

Email: sales@rcagency.com.au Ph: (07) 3216 2888 Fax: (07) 3216 2999

Opening Hour: 8:00am to 4:30pm Monday to Friday *Showroom by appointment only