LEDFL50 50W LED Flood Light (12V DC or 240V)









Description:

50W LED flood light in various characteristics suitable for in-door and out-door. Available in low voltage and 240V to suit various installation applications. Anti-corrosive version to suit for coastal environment. RGB Flood light (240V only) features colour changing option. RGB remote control included - controlled through radio frequency. Recommended Battery Model for RGB remote controller (not included) IS CR2025 Lithium 3V. Colour will reset if turned off via switch. Please use remote included.

Working Temperature: - 40° C to 55° C

Material: Aluminium (Standard and RGB version)

 $\label{eq:Aluminium} \textbf{Aluminium with anti-corrosion coating (Anti-Corrosion version)}$

Dimmable: No

Warranty: 2 years replacement only warranty

*Note: Low voltage versions are tested with our IP66 drivers. Cannot guarantee compatibility with all 12VDC transformers

IP	CRI	CRI
65	68	75
,	COOOL	20001/

Item Code	Body Type	Wattage	Input	Lumen Output	Beam	Colour Temp	Fitting Colour	Size L x W x H
LEDFL50	Standard	57W	240V	3800 Lm / 4000 Lm	100°	3000K / 6000K	Grey	290 x 236 x 150 mm
LEDFL50BK	Standard	57W	240V	3800 Lm / 4000 Lm	100°	3000K / 6000K	Black	360 x 285 x 110 mm
LEDFL50-LV	Standard	57W	12V DC	3800 Lm / 4000 Lm	100°	3000K / 6000K	Grey	290 x 236 x 150 mm
LEDFL50BK-LV	Standard	57W	12V DC	3800 Lm / 4000 Lm	100°	3000K / 6000K	Black	360 x 285 x 110 mm
LEDFL50-ANTC	Anti-Corrosive	57W	240V	3800 Lm / 4000 Lm	100°	3000K / 6000K	Black	290 x 236 x 150 mm
LEDFL50-AN-LV	Anti-Corrosive	57W	12V DC	3800 Lm / 4000 Lm	100°	3000K / 6000K	Black	290 x 236 x 150 mm
LEDFL50RGB	Standard	50W	240V	-	100°	RGB	Grey	288 x 238 x 150 mm

R&C AGENCY INTERNATIONAL

94 Wecker Road, Mansfield, QLD, 4122

Email: sales@rcagency.com.au Ph: (07) 3216 2888 Fax: (07) 3216 2999

Opening Hour: 8:00am to 4:30pm Monday to Friday *Showroom by appointment only