



ndard

Description:	80W LED flood light in various characteristics suitable for in-door and out-door. Also available in an Anti-corrosive version to suit for coastal environment.		
Working Temperature:	- 40° C to 55° C		
Material:	Aluminium (standard version) Aluminium with anti-corrosion coating (Anti-Corrosion version)		
Dimmable:	No	CRI	CRI
Warranty:	2 years replacement only warranty (does not cover any costs involved with installation/re-installation. 65	<u>6000к</u>	75 3000K

Item Code	Body Type	Wattage	Input	Lumen Output	Beam	Colour Temp	Fitting Colour	Face Size L x W	Size L x W x H
LEDFL80	Standard	91W	240V	6000 Lm / 6400 Lm	120°	3000K / 6000K	Black / Grey	285 x 235 mm	360 x 285 x 110 mm
LEDFL80-ANTC	Anti-Corrosive	91W	240V	6000 Lm / 6400 Lm	120°	3000K / 6000K	Black	285 x 235 mm	360 x 285 x 110 mm

## **R&C AGENCY INTERNATIONAL**

94 Wecker Road, Mansfield, QLD, 4122

Email: sales@rcagency.com.au Ph: (07) 3216 2888 Fax: (07) 3216 2999

Opening Hour: 8:00am to 4:30pm Monday to Friday \*Showroom by appointment only

Care is taken to ensure specifications are correct at time of production however R&C Agency reserves the right to change or modify specifications and product availability at any time without prior notification. \* Refer to our trade terms for full warranty conditions.