

F721/P
Polished Stainless Steel Wink




GRC Lighting

R & C Agency International
Lighting Specialists for over 15 years



F5060/RPM+T F5060/SPM+T
 Optional Premount Ring For
 Up Light Available



Description: In ground or wall mounted stainless steel eyelid.
 Material: 304 Stainless Steel, Tempered glass lens



Item Code	Max. Lamp Wattage	Lamp Base	Input	Fitting Colour	Size D x Depth	Cut Size D
F721/P	MR16 LED 5-10W	MR16	12V	Stainless Steel	97 x 110 mm	75 mm

MR16 LED Globe(s) to suit the fittings



LED20MR16



LED216-V4



LED216-V5




LEDMR165W
LEDMR1610W



LEDMR165W-IP65

Installation of Inground Lighting



Please ensure any inground light fitting is installed with adequate drainage and excess water does not accumulate beneath the fitting. Use some form of 10cm depth aggregate (gravel) for drainage.

Cable Connections for Inground & Exterior Lighting

IP68 connectors / weatherproof box must be used for installation of all exterior lights. Refer to page 188 for more information

R&C AGENCY INTERNATIONAL

94 Wecker Road,
 Mansfield, QLD, 4122

Email: sales@rcagency.com.au
 Ph: (07) 3216 2888
 Fax: (07) 3216 2999

Opening Hour:
 8:00am to 4:30pm Monday to Friday
 *Showroom by appointment only