

F5010 F5050 F5060 F5062 Uplight



GRE Lighting

R & C Agency International
Lighting Specialists for over 15 years



F5010



F5050
Solid brass die-cast



F5060
Stainless Steel



F5062
Stainless Steel



F5050SPM
Optional Premount Ring For F5050



F5060/RPM+T F5060/SPM+T
Optional Premount Ring
For F5010, F5060

Description: Small outdoor uplight providing uplight providing an elegant and compact appearance. Flush glass lens prevents water residual and dirt accumulation.

Material: F5010-Aluminium; F5050-Solid brass die-cast; F5060, F5062-316 Grade Stainless steel; Tempered Glass lens

Lamp Base: MR16



| Item Code | Max. Lamp Wattage | Input | Fitting Colour | Size DxH | Cut Size D |
|-----------|-------------------|-------|-----------------|---------------------------|------------|
| F5010 | MR16 LED 5-10W | 12V | Black | 98 x 100 mm | 75 mm |
| F5050 | MR16 LED 5-10W | | Brass | 98 x 100 mm | 75 mm |
| F5060/316 | MR16 LED 5-10W | | Stainless Steel | 97 x 100 mm | 75 mm |
| F5062/316 | MR16 LED 5-10W | | Stainless Steel | 97(L) x 97(W) x 100(H) mm | 75 mm |

MR16 LED Globe(s) to suit the fittings



LED20MR16



LED216-V4



LED216-V5




LEDMR165W
LEDMR1610W



LEDMR165W-IP65
LEDMR1610W

Installation of Inground Lighting



Please ensure any in-ground light fitting is installed with adequate drainage and excess water does not accumulate beneath the fitting. Use some form of 10cm depth aggregate (gravel) for drainage.

Cable Connections for Inground & Exterior Lighting

IP68 connectors / weatherproof box must be used for installation of all exterior lights. Refer to page 188 for more information

R&C AGENCY INTERNATIONAL

94 Wecker Road,
Mansfield, QLD, 4122

Email: sales@rcagency.com.au
Ph: (07) 3216 2888
Fax: (07) 3216 2999

Opening Hour:
8:00am to 4:30pm Monday to Friday
*Showroom by appointment only