



Description:

we recommend is 8 hours continuous use per day. Voltage drop occurs any length after 3m. After this point 12V DC Input Current 2166 mA LED per Series: 240 LEDs per metre LED Type: SMD 2835 Dimmable: Yes Comes with Adhesive Backing: Yes Maximum Single Run 3m Metre per Roll 5m

brightness will drop off gradually.

12V DC Open LED Strip Light. Available in 26W per metre. It is recommended that these are to stuck on metal material that can act as a heat sink. This is not recommended to be run at 24 hours per day, the maximum

TRIAC Dimmable Optional DALI DIMMABLE Optional DIMMABLE	
---	--

Item Code	Wattage/Metre	Lumen Output	Beam Angle	Colour Temp	LED Colour	Size W x H	Cuttable Size
LEDROPE12NW26WO	26W	2640 Lm / m	120°	4000K	Natural White	10 X 1.5 mm	12.5 mm

а т . . TM12VDC Tra

ransformers to suit	TM12VDC	IP Rated Transformers to s	TM12VDC Dimmable Transformers to suit			
Cut from 0-1 m Use TM12VDC60W		Cut from 0-1 m Use TM12VDC40WIPFT		Cut from 5-6 m Use TM12VDC192WIP		Cut from 0-3 m Use TM12VDC100WIPD
Cut from 2 m Use TM12VDC90W	A	Cut from 2 m Use TM12VDC60WIPFT	· .	Cut from 5-6 m Use TM12VDC200WIPFT		Cut from 4-6 m Use TM12VDC200WIPD
	P	Cut from 3 m Use TM12VDC100WIPFT	- mantana	Cut from 7-8 m Use TM12VDC264WIP		
		Cut from 4 m Use TM12VDC132WIP	-	Cut from 8-11 m Use TM12VDC360WIP		

R&C AGENCY INTERNATIONAL

94 Wecker Road, Mansfield, QLD, 4122

Email: sales@rcagency.com.au Ph: (07) 3216 2888 Fax: (07) 3216 2999

Opening Hour: 8:00am to 4:30pm Monday to Friday *Showroom by appointment only

Care is taken to ensure specifications are correct at time of production however R&C Agency reserves the right to change or modify specifications and product availability at any time without prior notification. * Refer to our trade terms for full warranty conditions.