



	Item Code	Wattage/Metre	Lumen Output	Beam Angle	Colour Temp	LED Colour	Size W x H	Cuttable Size
I	Metre per Roll	5m					DALI DIMMABLE DIMMABLE OPTION	Not the second s
I	Maximum Single Run	10m*					RIAC DALI 1-10	LOW LOW
(Comes with Adhesive Bac	king: Yes						
I	Dimmable:	Yes						
I	LED Type:	SMD 2835	5					
I	LED per Series:	60 LEDs p	er metre					
(Current	830 mA						
I	Input	24V DC						
I	Description:	point brig as a heat	24V DC Open LED Strip Light. Available in 10W per metre. Voltage drop occurs any length after 5m. After this point brightness will drop off gradually. It is recommended that these are to stuck on metal material that can act as a heat sink. This is not recommended to be run at 24 hours per day, the maximum we recommend is 8 hours continuous use per day. Can be put into Bar with diffuser.					

	Item Code	Wattage/Metre	Lumen Output	Beam Angle	Colour Temp	LED Colour	Size W x H	Cuttable Size
	LEDROPE24WW10WO	10W	1020 Lm/metre	120°	3200K	Warm White	8 x 1.5 mm	50 mm
TM24VDC Transformers to suit TM24VDC IP Rated Transformers to suit TM24VDC Dimmable Transformers to su								

Cut from 0-1 m	Cut from 0-3 m	Cut from 9-12 m	Cut from 0-8 m
Use TM24VDC24W	Use TM24VDC40WIPFT	Use TM24VDC150WIP	Use TM24VDC100WIPD
Cut from 2-4 m	Cut from 4 m	Cut from 13-16 m	Cut from 9-16 m
Use TM24VDC60W	Use TM24VDC60WIPFT	Use TM24VDC200WIPFT	Use TM24VDC200WIPFD
Cut from 5-9 m Use TM24VDC120W	Cut from 5-8 m Use TM24VDC100WIPFT	Cut from 17-19 m Use TM24VDC240WIP	

R&C AGENCY INTERNATIONAL

94 Wecker Road, Mansfield, QLD, 4122

Email: sales@rcagency.com.au Ph: (07) 3216 2888 Fax: (07) 3216 2999

Opening Hour: 8:00am to 4:30pm Monday to Friday *Showroom by appointment only

Care is taken to ensure specifications are correct at time of production however R&C Agency reserves the right to change or modify specifications and product availability at any time without prior notification. * Refer to our trade terms for full warranty conditions.