## **LEDROPE24CW9WN** 12W per Metre - 6000K IP54 24V Premium Strip Light





24V DC Premium LED Strip Light. Available in 12W per metre. Due to design of the strip and silicone used, colour Description:

shift occurs. Voltage drop occurs any length after 5m. After this point brightness will drop off gradually. \*It is recommended that these are to stuck on metal material that can act as a heat sink. This is not recommended to be run at 24 hours per day, the maximum we recommend is 8 hours continuous use per day. Can be put into Bar with diffuser. Any strip not mounted directly facing upwards towards ceiling should have extra adhesive

applied at intervals to ensure long term hold. 24V DC

LED per Series: 48 per metre (very noticeable spotting even in diffused bar)

LED Type: SMD 5050

Dimmable: Yes Comes with Adhesive Backing:

Input

Maximum Single Run 5m (any more will have voltage drop)

Metre per Roll 10m (tails both sides)

Item Code	Wattage/Metre	Lumen Output	Beam Angle	Colour Temp	LED Colour	Size W x H	Cuttable Size
LEDROPE24CW9WN	12W	960 Lm / Metre	120°	6000K	Cool White	10 x 2.3 mm	125 mm

TM24	VDC Transformers to suit	TM24VDC IP Rated Transformers to suit				TM24VDC Dimmable Transformers to suit		
	Cut from <b>0-1 m</b> Use TM24VDC24W		Cut from <b>0-2 m</b> <b>Use TM24VDC40WIPFT</b>		Cut from <b>7-10 m</b> Use TM24VDC150WIP		Cut from 0-6 m Use TM24VDC100WIPD	
	Cut from 2-4 m Use TM24VDC60W		Cut from 3-4 m Use TM24VDC60WIPFT		Cut from 11-13 m Use TM24VDC200WIPFT		Cut from <b>7-13 m</b> Use TM24VDC200WIPFD	
	Cut from 5-8 m Use TM24VDC120W				Cut from 14-16 m Use TM24VDC240WIP			

## **R&C AGENCY INTERNATIONAL**

94 Wecker Road, Mansfield, QLD, 4122

Email: sales@rcagency.com.au Ph: (07) 3216 2888 Fax: (07) 3216 2999

Opening Hour: 8:00am to 4:30pm Monday to Friday \*Showroom by appointment only