LEDROPE24RGBW IP20 20W per Metre 24V RGB Open Strip Light





Description:	m Fi ru ն Տ	24V DC Open LED Colour Changing Strip Light. Available in 20W per metre. RGBW(6000K) strip suitable for com- mercial and residential installations. Variety of control methods available including, DMX512, DALI DT6 and Radio Frequency. Standard 5 wire style PCB, compatible with most other 5 wire style receivers on the market. Suggested run times of 8-10 hours per day. It is recommended that these are to stuck on metal material that can act as a heat sink. This is not recommended to be run at 24 hours per day, the maximum we recommend is 8 hours contin- uous use per day. If butting runs up in configurations like long straight runs, or rectangles especially, there will be slight differences in intensity due to voltage drop. To minimize this, we suggest using a thicker gauge cable, please consult with our sales team if you're not sure.					
LED per Series:		60 per metre					
LED Type:		SMD 5050					
Dimmable:		Yes, via RGB controller [see LEDRGBW12/24CON or LEDRGBWCONKIT]					
RGB Requirement:		Require RGB controller [see LEDRGBW12/24CON or LEDRGBWCONKIT]					
Comes with Adhesive Backing:		Yes					
Maximum Single Run:		3m					
Metre per Roll:		6m 20					
Item Code	Wattage/Metre		Input	Beam Angle	LED Colour	Size W x H	Cuttable Size
LEDROPE24RGBW20	20W		24V DC	120°	RGBW	12 x 3 mm	100 mm

R&C AGENCY INTERNATIONAL

94 Wecker Road, Mansfield, QLD, 4122

Email: sales@rcagency.com.au Ph: (07) 3216 2888 Fax: (07) 3216 2999

Opening Hour: 8:00am to 4:30pm Monday to Friday *Showroom by appointment only

Care is taken to ensure specifications are correct at time of production however R&C Agency reserves the right to change or modify specifications and product availability at any time without prior notification. * Refer to our trade terms for full warranty conditions.