## **D222-R** IP44 Recessed Downlight with Mirrored Reflector





Description: Designed with state of art heat sink providing high lumen package and lifespan of 50,000 hours. IP44 protection glass on the front, very easy for cleaning. Narrow to wide beam reflectors ready for different applications. Cut off angle more than 25° offering good glaring control. UGR <19. Easily installed with two spring on the side. Robust and clean European design is the best selection for project business. Please note: Actual products should be used to confirm all cut hole sizes prior to installation

LED Type: COB LED Chip

Material: Aluminium

Dimmable: Yes, dimmable driver + flex & plug



Item Code	Wattage	Input	Lumen Output	Beam	ССТ	Fitting Colour	Size D x H	Cut Size D
D222-R-18W	18W	500mA, 36V	2400 Lm / 2500 Lm / 2575 Lm	20° / 70°	2700K / 3000K / 4000K	Black / White	165 x 133 mm	150 mm
D222-R-25W	25.5W	700mA, 36V	3264 Lm / 3400 Lm / 3502 Lm	20° / 70°	2700K / 3000K / 4000K	Black / White	165 x 133 mm	150 mm
D222-R-34W	34W	900mA, 37V	4032 Lm / 4200 Lm / 4326 Lm	20° / 70°	2700K / 3000K / 4000K	Black / White	165 x 133 mm	150 mm

## **R&C AGENCY INTERNATIONAL**

94 Wecker Road, Mansfield, QLD, 4122

Email: sales@rcagency.com.au Ph: (07) 3216 2888 Fax: (07) 3216 2999

Opening Hour: 8:00am to 4:30pm Monday to Friday \*Showroom by appointment only

Care is taken to ensure specifications are correct at time of production however R&C Agency reserves the right to change or modify specifications and product availability at any time without prior notification. \* Refer to our trade terms for full warranty conditions.