D220-R IP44 Recessed Downlight with Mirrored Reflector





Description: Designed with state of art heat sink providing high lumen package and lifespan of 50,000 hours. IP44 protection glass on the front,

very easy for cleaning. Narrow to wide beam reflectors ready for different applications. Cut off angle more than 25° offering good glaring control. UGR <19. Easily installed with two spring on the side. Robust and clean European design is the best selection for project business. Please note: Actual products should be used to confirm all cut hole sizes prior to installation

LED Type: COB LED Chip Material: Aluminium

Dimmable: Yes, dimmable driver + flex & plug









1-10V
DIMMABL

Item Code	Wattage	Input	Lumen Output	Beam	Colour Temperature	Fitting Colour	Size D x H	Cut Size D
D220-R-13W	13W	350mA, 36V	1500 Lm / 1545 Lm	24° / 50°	3000K / 4000K	Black / White	138 x 101 mm	125 mm
D220-R-17W	17.5W	500mA, 35V	2100 Lm / 2163 Lm	24° / 50°	3000K / 4000K	Black / White	138 x 101 mm	125 mm
D220-R-25W	25W	700mA, 36V	2900 Lm / 2987 Lm	24° / 50°	3000K / 4000K	Black / White	138 x 101 mm	125 mm

R&C AGENCY INTERNATIONAL

94 Wecker Road, Mansfield, QLD, 4122

Email: sales@rcagency.com.au Ph: (07) 3216 2888 Fax: (07) 3216 2999

Opening Hour: 8:00am to 4:30pm Monday to Friday *Showroom by appointment only