D070-R D071-R D072-R D073-R Modular Downlight with Tilt & Rotatory **Function**





Description:

Modular downlight family featuring ultimate flexibility and lighting options. Available in a range of wattages (from 6W to 34W), and Cut Size (75 to 150mm). Suitable for replacing halogen, PLC and metal halide. Available in various beam angle options. Optional gold reflector and honeycomb accessories available for upmarket and specialist installations. COB LED technology produces CRI output >90. 355° rotation and 30° tilt make it an effective downlight, directional light or wall

LED Type: COB LED Material: Aluminium

Dimmable: Yes, with selected dimmers

Include Driver: Yes, dimmable driver + flex & plug D071-R: 15° available on request D072-R: 20° available on request Optional Beam:

D073-R: 20° available on request













Item Code	Wattage	Input	Lumen Output	Beam	сст	Fitting Colour	Size D x H	Cut Size D
D069-R	6W	350mA, 17V	600 Lm / 618 Lm	24°/36°/50°	3000K / 4000K	Black / White	80 x 67 mm	68 mm
D070-R	9W	500mA, 18V	900 Lm / 927 Lm	24°/36°/50°	3000K / 4000K	Black / White	85 x 67 mm	75 mm
D071-R	13W	350mA, 36V	1300 Lm / 1339 Lm	36°/24°	3000K / 4000K	Black / White	115 x 100 mm	100 mm
D072-R	26W	700mA, 37V	2784 Lm / 2900 Lm / 2987 Lm	30°/ 40°/ 70°	2700K / 3000K / 4000K	Black / White	145 x 136 mm	125 mm
D073-R	34W	900mA, 37V	3360 Lm / 3500 Lm / 3605 Lm	30°/40°/70°	2700K / 3000K / 4000K	Black / White	165 x 145 mm	150 mm