

D060-R D061-R D062-R D063-R
High Power Recessed Downlight



GRC Lighting
R & C Agency International
Lighting Specialists for over 15 years



Description: This series of downlight features a state-of-the-art heat sink providing ample heat dissipation for up to 5500Lm output. IP54 from the front and transparent glass for easily cleaned front and wide range of install scenarios. Anti-glare design with over 30° cut-off angle coupled with deep front frame for visual comfort.

LED Type: COB LED

Material: Aluminium

Dimmable: D060-R: Yes
D061-R-34W: Yes
D061-R-52W: No
D062-R: No
D063-R: No

Include Driver: Yes, with flex & plug

Optional Beam: D060-R: 10°, 40° available on request
D061-R: 10° available on request
D062-R: 10° available on request
D063-R: 10° available on request



| Item Code | Wattage | Input | Lumen Output | Beam | CCT | Fitting Colour | Size D x H | Cut Size D |
|------------|---------|------------|-----------------------------|-----------|-----------------------|----------------|--------------|------------|
| D060-R-18W | 18W | 500mA, 36V | 2016 Lm / 2100 Lm / 2163 Lm | 20° / 70° | 2700K / 3000K / 4000K | Black / White | 139 x 105 mm | 125 mm |
| D060-R-34W | 34W | 900mA, 37V | 3264 Lm / 3400 Lm / 3502 Lm | 20° / 70° | 2700K / 3000K / 4000K | Black / White | 139 x 105 mm | 125 mm |

| Item Code | Wattage | Input | Lumen Output | Beam | CCT | Fitting Colour | Size D x H | Cut Size D |
|------------|---------|-------------|-----------------------------|-----------------|-----------------------|----------------|--------------|------------|
| D061-R-18W | 18W | 500mA, 37V | 2016 Lm / 2100 Lm / 2163 Lm | 20° / 40° / 70° | 2700K / 3000K / 4000K | Black / White | 165 x 132 mm | 150 mm |
| D061-R-34W | 34W | 900mA, 37V | 3360 Lm / 3500 Lm / 3605 Lm | 20° / 40° / 70° | 2700K / 3000K / 4000K | Black / White | 165 x 132 mm | 150 mm |
| D061-R-52W | 52W | 1400mA, 37V | 5280 Lm / 5500 Lm / 5665 Lm | 20° / 40° / 70° | 2700K / 3000K / 4000K | Black / White | 165 x 132 mm | 150 mm |

| Item Code | Wattage | Input | Lumen Output | Beam | CCT | Fitting Colour | Size D x H | Cut Size D |
|------------|---------|-------------|-------------------|-----------------|---------------|----------------|--------------|------------|
| D062-R-52W | 52W | 1400mA, 37V | 5500 Lm / 5665 Lm | 20° / 40° / 70° | 3000K / 4000K | Black / White | 200 x 145 mm | 175 mm |

| Item Code | Wattage | Input | Lumen Output | Beam | CCT | Fitting Colour | Size D x H | Cut Size D |
|------------|---------|-------------|-------------------|-----------------|---------------|----------------|--------------|------------|
| D063-R-52W | 52W | 1400mA, 37V | 5500 Lm / 5665 Lm | 20° / 40° / 70° | 3000K / 4000K | Black / White | 220 x 155 mm | 200 mm |

R&C AGENCY INTERNATIONAL

94 Wecker Road,
Mansfield, QLD, 4122

Email: sales@rcagency.com.au
Ph: (07) 3216 2888
Fax: (07) 3216 2999

Opening Hour:
8:00am to 4:30pm Monday to Friday
*Showroom by appointment only