


D322-R

IP20 10W 3-Colour Switch-able
Polycarb Downlight



GRC Lighting

R & C Agency International
Lighting Specialists for over 15 years



Use this integrated switch to select colour temperature prior installation

OPTIONAL CONVERSION PLATE

G800N/GWH-LTN

To cover hole of 127-195 mm

G801/GWH-LT

To cover hole of 110-145 mm

G802N/GWH-LT

To cover hole of 178-210 mm

G803N/GWH-LT

To cover hole of 225-265 mm

Description: All purpose IP44 (front only), IC-4 dimmable LED downlight suitable for commercial and residential installations. High lumen output, the integrated switch allows for easy changing of colour temperature. 95 degree beam angle. Inbuilt LED driver with flex and plug, for simple installation and future maintenance.

LED Type: SMD LED

Material: Polycarb

Lens: Frost lens

Dimmable: Yes

Include Driver: Yes

Fitting Colour: White



Item Code	Wattage	Input	Lumen Output	Beam	Colour Temp	Size D x H	Cut Size D
D322-R	10W	120mA, 72V	800 Lm, 900 Lm, 860 Lm	95°	Adjustable between 3000K, 4000K, 5000K	110 x 68 mm	90 mm

R&C AGENCY INTERNATIONAL

94 Wecker Road,
Mansfield, QLD, 4122

Email: sales@rcagency.com.au
Ph: (07) 3216 2888
Fax: (07) 3216 2999

Opening Hour:
8:00am to 4:30pm Monday to Friday
*Showroom by appointment only