LED134 LED137 Premium 20W **Downlight in Round**







LED134

Description: 20W Commercial grade round LED Downlight available in fixed and gimble styles.

LED Type: SMD LED

Material: Aluminium Body

Dimmable: Yes

Include Driver: Yes, with Flex & Plug

Mounting Method:

*Please note, Dimmable with RCADIMMERHD200T.

*Optional: C-Bus System Compatible (Leading Edge). 6 per channel.











| Item Code | Wattage | Input | Lumen Output | Beam Angle | Colour Temperature | Fitting Colour | Size D x H | Cut Size D |
|--------------|---------|------------|--------------|------------|--------------------|------------------------|------------|------------|
| LED134R-CWFP | 20W | 700mA, 24V | 1100 Lm | 120° | 6000k | Black / Silver / White | 110 x 85mm | 90 mm |
| LED134R-WWFP | 20W | 700mA, 24V | 950 Lm | 120° | 3000k | Black / Silver / White | 110 x 85mm | 90 mm |
| LED137R-CWFP | 20W | 700mA, 24V | 1100 Lm | 120° | 6000k | Silver / White | 110 x 85mm | 90 mm |
| LED137R-WWFP | 20W | 700mA, 24V | 950 Lm | 120° | 3000k | Silver / White | 110 x 85mm | 90 mm |

Optional conversion plates to suit LED134 & LED137



G802N/GWH-LT











G803N/GWH-LT

LED134R+ LED137R+ G803N/GWH-LT G803N/GWH-LT

| Item Code | Size of Downlight Cut Size to fit | Size of Downlight Trim to fit | Minimum Hole conversion can cover | Maximum Hole conversion plate can cover | Conversion plate Overall Size |
|--------------|--------------------------------------|-------------------------------|-----------------------------------|---|----------------------------------|
| G802N/GWH-LT | 95 mm | 113 mm | 178 mm | 210 mm | 230 mm |
| G803N/GWH-LT | 95 mm | 113 mm | 225 mm | 265 mm | 270 mm |

R&C AGENCY INTERNATIONAL

94 Wecker Road, Mansfield, QLD, 4122

Email: sales@rcagency.com.au Ph: (07) 3216 2888 Fax: (07) 3216 2999

Opening Hour: 8:00am to 4:30pm Monday to Friday *Showroom by appointment only