

|  |   | LED843L      |        |                       | LED843P                |                           | LED843R        |                   |     |    |                |  |
|--|---|--------------|--------|-----------------------|------------------------|---------------------------|----------------|-------------------|-----|----|----------------|--|
| Description:   | 1W LED wall light wtih clip on face. Lourved, Plain and Ribbed avaialble.             |              |        |                       |                        |                           |                |                   |     |    |                |  |
| LED Type:  | СОВ   |              |        |                       |                        |                           |                |                   |     |    |                |  |
| Material:  | Aluminium/Frost Diffuser  |              |        |                       |                        |                           |                |                   |     |    |                |  |
| Include Driver:  | Νο  |              |        |                       |                        |                           |                |                   |     |    |                |  |
| Mounting Method:   | Recessed Date TRIAC DALL Diversity Development Date Date Date Date Date Date Date Dat |              |        |                       |                        |                           |                |                   |     |    |                |  |
| Wiring Method:   | Series Connection for 350mA.Parallel Connection for 12V                               |              |        |                       |                        |                           |                |                   |     |    |                |  |
| Item Code  | Item Code   |              | Input  |                       | Colour Temperature     |                           | Fitting Colour | · Size L x W x H  |     |    | Cut Size L x W |  |
| LED843-GR12V   |   | 114/         | 12V DC |                       | 3000K / 6000K / Blue / |                           | C              | 000024            |     |    | 00 00          |  |
| LED843-GR350MA   |   | 1W           | 350mA  |                       | Green / Red            |                           | Grey           | 90 x 90 x 34 mm   |     | 'n | 80 x 80 mm     |  |
| 350mA LED DRIVER (s) to suit 1W fittings 12V LED Transformer/s to suit 1W fittings |   |              |        |                       |                        |                           |                |                   |     |    |                |  |
| Non-Dimmable Drivers   | Dimmable Drivers  |              |        | IP20 LED Transformers |                        | IP rated LED Transformers |                |                   |     |    |                |  |
| CODE   | QTY   | CODE         |        | QTY                   | CODE                   | QTY                       | CODE           |                   | QTY |    |                |  |
| LEDDRIVER9350KL  | 3   | LEDDR16350DT |        | 5                     | TM12VDC4.2W            | 3                         | TM12VDC40V     | 240WIPFT 3        |     |    |                |  |
| LEDDRIVER12350   | 4   | LEDDR28350DT |        | 9                     | TM12VDC8.4W            | 6                         | TM12VDC60V     | TM12VDC60WIPFT 48 |     |    |                |  |
| LEDDRIVER24350   | 8   | LEDDR45350DT |        | 15                    | TM12VDC12W/T           | 9                         |                |                   |     |    |                |  |
| LEDDR37350IP   | 12  |              |        |                       | TM12VDC12W/TD          | 9                         |                |                   |     |    |                |  |

\* Must be wired in series

\* When running multiple fittings, driver must be loaded up to prevent any fault caused by underloading.

Any fittings that are being wired together to run more than one fitting to one driver will have their warranty void if the quick connect plugs are cut-off. Available are quick connect adapter available in two plug, three plug and six plug options to suit 350mA or 700mA constant current fittings.



## **R&C AGENCY INTERNATIONAL**

94 Wecker Road, Mansfield, QLD, 4122

Email: sales@rcagency.com.au Ph: (07) 3216 2888 Fax: (07) 3216 2999

Opening Hour: 8:00am to 4:30pm Monday to Friday \*Showroom by appointment only

Care is taken to ensure specifications are correct at time of production however R&C Agency reserves the right to change or modify specifications and product availability at any time without prior notification. \* Refer to our trade terms for full warranty conditions.