



Item Code	Wattage	Input	Lumen Output	Beam Angle	Colour Temperature	Fitting Colour	Size L x W x H	Cut Size I	LxW
Include Driver: Yes *Photometric available upon request 20 90									90
Include Driv								IP	CRI
Dimmable:	N	D							
Material:	Al	uminium							
LED Type:	CC	DB							
Description	sp	3W Wall Recessed light. Luminaire designed with good glaring control and comfortable light output. Easy to install with two spring on up & down. No UV or IR radiation. Designed for decorative light and guide light, good for hall, corridor, residential and commercial application.							

Item Code	Wattage	Input	Lumen Output	Beam Angle	Colour Temperature	Fitting Colour	Size L x W x H	Cut Size L x W
W0066	3W	700mA, 4.2V	170 Lm / 175 Lm	80°	3000К / 4000К	White	105 x 35 x 32 mm	100 x 30 mm

## **R&C AGENCY INTERNATIONAL**

94 Wecker Road, Mansfield, QLD, 4122

Email: sales@rcagency.com.au Ph: (07) 3216 2888 Fax: (07) 3216 2999

Opening Hour: 8:00am to 4:30pm Monday to Friday \*Showroom by appointment only

Care is taken to ensure specifications are correct at time of production however R&C Agency reserves the right to change or modify specifications and product availability at any time without prior notification. \* Refer to our trade terms for full warranty conditions.