



F71X/PREMOUNT Optional box

Description: IP44 Low profile frame, frost glass diffuser. Flush Allen Key screws. In-built 6W LED.

LED Type:

Dimmable: 350mA version: Optional ; 24V DC version: No

Include Driver: Yes

P 44	Dimmable Optional	DALI DIMMABLE OPTION	1-10 DIMMAB OPTION		
	CONSTANT CURRENT ON				

Item Code	Wattage	Input	Lumen Output	Beam Angle	Colour Temperature	Fitting Colour	Size L x W x H	Cut Size L x W
F712-LED	CINI	250-4 / 24// DC	520 Jan / 650 Jan	120%	20504 / 60004	M/hite Disels	250 (0 (2	220 40
F713-LED	6W 350	350mA / 24V DC 520 Lm / 650 Lm	120	3050K / 6000K	white, Black	250 x 69 x 62 mm	220 x 49 mm	

24V LED Transformer/s to suit 6W fittings

SMD

IP20 LED Transformers		IP rated LED Transformers		
CODE	QTY	CODE	QTY	
TM24VDC20W/TD	2	TM24VDC40WIPFT	5	
TM24VDC25W/T	3	TM24VDC60WIPFT	8	
TM24VDC50W	6	TM24VDC100WIPFT	13	

R&C AGENCY INTERNATIONAL

94 Wecker Road, Mansfield, QLD, 4122

Email: sales@rcagency.com.au Ph: (07) 3216 2888 Fax: (07) 3216 2999

Opening Hour: 8:00am to 4:30pm Monday to Friday *Showroom by appointment only