

**CUSTOM MADE SUSPENDED EXTRUSION  
LEDBARP-5075**



Made to order, customised Aluminium profile available as either surface mount or pendant ready to install. Innovative design that allows for direct and in-direct lighting options. This item can be ordered in Pendant format in Direct and Indirect, or just Direct. Available in either black, white, or silver. Frosted opaque polycarbonate diffuser pre-installed for clean, smooth diffusion of LED light source for 'no visible dot' aesthetic. Option for CRI90 available for superior colour rendering for home, office or shop-fit. This profile features a quick clip-in tray system that allows easy installation and future servicing of item by electrician.

Powered by Osram LED technology (refer to separate documentation which may differ project to project depending on requirements.)

Dimming options available in: non-dimmable and DALI options.

**NB: Lumen package is advertised as source cold lumens, no IES/Photometric is available for total fitting.**

Assembled in Australia, with parts from Australia and International suppliers.

<b>Code</b>	Bar: LEDBARP5075 Module: *Refer to project specification* Driver: *Refer to project specification*
<b>Wattage</b>	Approximately 28w per 1.12m
<b>Material</b>	Aluminum
<b>Input</b>	240v AC
<b>Fitting Colour</b>	Black/White/Silver
<b>Colour Temperature</b>	3000K or 4000K
<b>CRI</b>	<b>CRI80 standard</b> / CRI90 optional
<b>Lumen Output at chip</b>	Up to 4200 lumen per 1.12m ( <i>undiffused lumen</i> )
<b>Beam Angle</b>	100°
<b>Dimmable</b>	<b>Standard: Non-Dimmable</b>
<b>IP Rating</b>	IP20
<b>Overall Size</b>	Max Single Length: as per project specification (up to 2820mm) Width: 50mm Height: 75mm
<b>Warranty</b>	5 year back to base warranty <b><u>(Does not cover ANY costs involved with installation/ reinstallation).</u></b>

