

D080-R D081-R D082-R D083-R High Power Recessed Downlight



GRE Lighting

R & C Agency International
Lighting Specialists for over 15 years



D080-R



D081-R



D082-R



D083-R

Description: New 2024 release Tri-Colour Switchable commercial downlight that is available in four sizes spanning from 125, up to 225mm cutout sizes allowing for a uniformity across multiple room installations. IP54 from front for flexible installation scenarios. The anti-glare, recessed design has an over 30° cut-off angle for superior visual comfort over traditional opaque lens downlight designs. Bundled with a non-dimmable dip switchable constant current driver which can be changed to as low as 13w* - Lower wattage customisations are also available for special case installations - please enquire with sales team.

LED Type: COB LED

Material: Aluminium

Dimmable: Standard, non-dim

Include Driver: Yes, with flex & plug

Optional Beam: 24°

Warranty: 3 year replacement only warranty



Item Code	Wattage	Input	Lumen Output	Beam	CCT	Fitting Colour	Size D x H	Cut Size D
D080-R-38W	38W	900mA, 44V	3100-3400lm*	60 °r 24°	Tri Swtich 3K/4K/5K	Black / White	140 x 113 mm	125-135 mm

Item Code	Wattage	Input	Lumen Output	Beam	CCT	Fitting Colour	Size D x H	Cut Size D
D081-R-38W	38W	900mA, 44V	3100-3400lm*	60 °r 24°	Tri Swtich 3K/4K/5K	Black / White	170 x 132 mm	150-165 mm

Item Code	Wattage	Input	Lumen Output	Beam	CCT	Fitting Colour	Size D x H	Cut Size D
D082-R-34W	38W	900mA, 44V	3100-3400lm*	60 °r 24°	Tri Swtich 3K/4K/5K	Black / White	200 x 133 mm	175-195 mm

Item Code	Wattage	Input	Lumen Output	Beam	CCT	Fitting Colour	Size D x H	Cut Size D
D083-R-52W	38W	900mA, 44V	3100-3400lm*	60 °r 24°	Tri Swtich 3K/4K/5K	Black / White	230 x 138 mm	200-225 mm

*Lumen rating UP TO 3100 lumen for 3000 and 5000k settings, 3400 lumen rating for 4000k rating

R&C AGENCY INTERNATIONAL

94 Wecker Road,
Mansfield, QLD, 4122

Email: sales@rcagency.com.au
Ph: (07) 3216 2888
Fax: (07) 3216 2999

Opening Hour:
8:00am to 4:30pm Monday to Friday
*Showroom by appointment only