



Compact multi output constant current phase cut dim-mable driver suitable for driving a range of LED prod-ucts. Multiple fittings connected to 1 driver need to be wired in Series, unless otherwise instructed.

ORDERING CODE	LEDDR40400/550D
LEDRGBRE5IN1	220-240V AC
INPUT	25-40v DC (22-28w)
	400/450/500/550mA (Set via Dipswitch)
SIZE	106 x 46 x 31mm
WARRANTY	2 Years
IP RATING	20
OPERATING TEMPERATURE	-30°c— 50°c* Lifetime will drop significantly if case tempera-ture continues to operate at temperatures of 60°C— Ideally allow for good ventilation.
CONNECTION TYPE	Terminals
DIMMABLE	Yes—suggested is MEDM DIGINET
NOTES	It is the installer's responsibility to ensure the voltage window and current will suit the intended LED luminaire. Installer is to set the dipswitch setting to allow for required current output.

R&C AGENCY INTERNATIONAL

94 Wecker Road, Mansfield, QLD, 4122

Email: sales@rcagency.com.au Ph: (07) 3216 2888 Fax: (07) 3216 2999

Opening Hour: 8:00am to 4:30pm Monday to Friday *Showroom by appointment only

Care is taken to ensure specifications are correct at time of production however R&C Agency reserves the right to change or modify specifications and product availability at any time without prior notification. * Refer to our trade terms for full warranty conditions.