



Description:Diecast aluminium 1.2W LED Recessed cabinet Light.Material:Diecast Aluminium BodyInclusion:50cm lead with connectorDimmable:Yes, if using dimmable driverInclude Driver:No

Wiring Method: Series Connection for 350mA, Parallel Connection for 12V



Item Code	Wattage	Input	Lumen Output	Beam Angle	Colour Temperature	Fitting Colour	Size D x H	Cut Size D
LED301N	1.2W	350mA	64 Lm	50°	6000К 3000К	Anodised Aluminium	42 x 22 mm	35 mm
LED301N-12V	3.5W	12V DC	53 Lm	50*				

350mA LED DRIVER (s) to suit 1.2W fittings

Non-Dimmable Drivers		Dimmable Drivers		
CODE	QTY	CODE	QTY	
LEDDRIVER9350KL	2	LEDDR16350DT	4	
LEDDRIVER12350	3	LEDDR28350DT	9	
LEDDRIVER24350	7	LEDDR43350DT	13	
LEDDR37350IP	12			

IP20 LED Transformers				
CODE	QTY			
TM12VDC4.2W	1			
TM12VDC8.4W	2			
TM12VDC12W/T	3			

* Must be wired in series

* When running multiple fittings, must be loaded up to prevent any fault caused by underloading.

Any fittings that are being wired together to run more than one fitting to one driver will have their warranty void if the quick connect plugs are cut-off. Available are quick connect adapter available in two plug, three plug and six plug options to suit 350mA or 700mA constant current fittings.



R&C AGENCY INTERNATIONAL

94 Wecker Road, Mansfield, QLD, 4122

Email: sales@rcagency.com.au Ph: (07) 3216 2888 Fax: (07) 3216 2999

Opening Hour: 8:00am to 4:30pm Monday to Friday *Showroom by appointment only

Care is taken to ensure specifications are correct at time of production however R&C Agency reserves the right to change or modify specifications and product availability at any time without prior notification. * Refer to our trade terms for full warranty conditions.