

LEDFL10RGBBK24V
24v DC RGB+CCT 10w IP65
RF Control Floodlight



GRC Lighting

R & C Agency International
Lighting Specialists for over 15 years



Description:	24v DC Low Voltage RGB+CCT (Colour Tune) Floodlight designed for a variety of applications. Requires 2 core cable installation only (unlike traditional RGB/RGBW lighting) - making it an excellent choice for upgrade of existing mono-colour lighting. Integrated RGB+CCT receiver features in-built signal forwarding technology allowing UP TO 30m between fittings of the same family to be controlled with the same hand remote.
Material:	Aluminium
Input	24v DC (Requires Remote transformer, not included in box), allow up to 20w when calculating for transformers.
Output	Up to** 10w - 900 lumen (full output all channel mix mode) Alternate operation modes (eg single colour mode will be <3w, dual colour mode will be <6w)
Beam Angle	160 ° Wide Flood Beam
Operation modes	*Stand alone RGB *Stand alone Colour Tuneable (Extra Warm White -> Daylight *RGB+White Mix
IP Rating	65 only (Ensure all cable junctions are complete to IP68 standard or warranty is void)
Dimmable	Via Hand Controller (LEDRGBCON8ZONE)
Warranty	2 Year Replacement Only
Size	Overall 107 (W) x 166 (H) x 32mm (D)
Additional	All distances are theoretical maximums, and assumed to be open areas with no interference sources. Over very large distances colour change modes MAY experience mis-timings with synchronisation in the event of weak signal between devices.



LEDRGBCON8ZONE (PURCHASED SEPERATELY)



Also available:
 24vdc 9w 15 degree tight beam spike spot in RGB+CCT - ideal for lighting up columns, poles and skinny tall trees of up to 10m height.

R&C AGENCY INTERNATIONAL

94 Wecker Road,
 Mansfield, QLD, 4122

Email: sales@rcagency.com.au
 Ph: (07) 3216 2888
 Fax: (07) 3216 2999

Opening Hour:
 8:00am to 4:30pm Monday to Friday
 *Showroom by appointment only